

Appl. No.: 10/774,821
Reply to Office Action of: 05/29/2008

RECEIVED
CENTRAL FAX CENTER
AUG 05 2008

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) An ~~electronic device~~ apparatus comprising:

a device printed wiring board;

an electrical connector connected to the device printed wiring board;

a camera coupled to the device printed wiring board by the electrical connector at a stepless movement height connection,

wherein the stepless movement height connection allows the camera to slide relative to the electrical connector along a first axis to allow positioning of the camera relative to the electrical connector at one of a plurality of different heights along the first axis, wherein the stepless movement height connection extends beyond a height of the electrical connector along the first axis, wherein the plurality of different heights extends along a majority of a height of the camera, and wherein the majority of the height of the camera is greater than a height of the electrical connector.

2. (Currently amended) ~~As An apparatus electronic device~~ as in claim 1 wherein the ~~electronic device~~ apparatus comprises a hand-held portable electronic device.

Appl. No.: 10/774,821

Reply to Office Action of: 05/29/2008

3. (Currently amended) An ~~electronic device~~ apparatus as in claim 1 wherein the electronic device comprises a mobile telephone.

4. (Currently amended) An ~~electronic device~~ apparatus as in claim 1 wherein the electrical connector comprises a camera receiving slot with electrical contacts extending into the camera receiving slot, and wherein the camera is located in the camera receiving slot.

5. (Currently amended) An ~~electronic device~~ apparatus as in claim 1 wherein the device printed wiring board comprises a slot, and wherein the camera extends through the slot.

6. (Currently amended) An ~~electronic device~~ apparatus as in claim 5 wherein the camera comprises spring contacts and the electrical connector comprises substantially stationary conductors, and wherein the spring contacts are adapted to slide along the substantially stationary conductors when the camera is inserted into the electrical connector and into the slot of the device printed wiring board.

7. (Currently amended) An ~~electronic device~~ apparatus as in claim 1 wherein the camera comprises a housing and electrical conductors on the housing, wherein the electrical conductors extend along a first lateral exterior side of the housing.

8. (Currently amended) An ~~electronic device~~ apparatus as in claim 7 wherein the electrical conductors extend along an opposite second lateral exterior side of the housing, and wherein the electrical connector comprises contacts located in a camera receiving slot of the electrical connector and

Appl. No.: 10/774,821

Reply to Office Action of: 05/29/2008

electrically contacting the electrical conductors on the first and second lateral sides of the housing of the camera.

9. (Currently amended) An ~~electronic device~~ apparatus as in claim 7 wherein the electrical conductors extend along an adjacent side of the housing, wherein the camera comprises a camera printed wiring board attached to the electrical conductors on the adjacent side of the housing.

10. (Currently amended) An ~~electronic device~~ apparatus as in claim 1 wherein the electrical connector comprises a housing having a general ring shape with a center camera receiving slot, and electrical spring contacts extending into the camera receiving slot from opposite sides of the general ring shape.

11. (Currently amended) An ~~electronic device~~ apparatus as in claim 1 wherein the camera extends through the electrical connector in a general substantially stationery telescoping arrangement.

12. (Currently amended) A ~~portable electronic device camera~~ An apparatus comprising:

a housing;

camera optics and electronics inside the housing;

electrical conductors extending along a rear end of the housing and along a first lateral side of the housing; and

a camera printed wiring board stationarily connected to the rear end of the housing and coupled to the electrical conductors,

Appl. No.: 10/774,821

Reply to Office Action of: 05/29/2008

wherein the electrical conductors are adapted to be removably connected to contacts of an electrical connector located along the first lateral side of the housing, and wherein a height of the electrical conductors along the first lateral side of the housing is sized and shaped to be greater than a height of the electrical connector when the camera apparatus is connected to the electrical connector.

13. (Currently amended) ~~A portable electronic device camera~~ An apparatus as in claim 12 wherein the electrical conductors extend along a second opposite lateral side of the housing.

14. (Currently amended) ~~A portable electronic device camera~~ An apparatus as in claim 13 wherein the electrical conductors comprises metallized conductor paths along exterior sides of the housing.

15. (Currently amended) ~~A portable electronic device camera~~ An apparatus as in claim 12 wherein the electrical conductors extend along an adjacent side of the first lateral side, and wherein the camera printed wiring board is electrically connected to the electrical conductors on the adjacent side.

16. (Currently amended) ~~A portable electronic device camera~~ An apparatus as in claim 12 wherein the electrical conductors along the first lateral side are adapted to slide along the contacts of the electrical connector in a first axis of insertion of the ~~portable electronic device camera~~ apparatus into the electrical connector to provide an adjustable height connection of the ~~portable electronic device camera~~ apparatus to the electrical connector.

Appl. No.: 10/774,821

Reply to Office Action of: 05/29/2008

17. (Currently amended) ~~A portable electronic device camera~~ An apparatus as in claim 12 wherein an image inlet aperture is located at a front end of the housing.

18. (Currently amended) ~~A mobile telephone~~ An apparatus comprising:

a mobile telephone printed wiring board; and

~~a portable electronic device camera~~ an apparatus as in claim 12 coupled to the mobile telephone printed wiring board by an electrical connector.

19. (Currently amended) ~~A printed wiring board and electrical connector subassembly~~ An apparatus comprising:

a mobile telephone printed wiring board having a transceiver attached to the mobile telephone printed wiring board; and

a camera electrical connector attached to the mobile telephone printed wiring board,

wherein the camera electrical connector comprises a camera receiving area adapted to receive a camera therein and make electrical contact at one of a plurality of different locations along a majority of a height of the camera inside the camera receiving area, wherein a height of the camera receiving area is sized and shaped to be less than a height between the plurality of different locations along the majority of the height of the camera when the camera is received in the camera receiving area, and wherein the camera

Appl. No.: 10/774,821

Reply to Office Action of: 05/29/2008

receiving area comprises a through hole extending entirely through a housing of the camera electrical connector.

20. (Currently amended) ~~A printed wiring board and electrical connector subassembly~~ An apparatus as in claim 19 wherein the camera electrical connector comprises spring contacts extending into the camera receiving area from a first lateral side of the camera receiving area.

21. (Currently amended) ~~A printed wiring board and electrical connector subassembly~~ An apparatus as in claim 20 wherein the spring contacts extend into the camera receiving area from a second opposite lateral side of the camera receiving area.

22. (Currently amended) ~~A printed wiring board and electrical connector subassembly~~ An apparatus as in claim 20 wherein the camera electrical connector comprises a housing with a general ring shape and wherein the camera receiving area is located inside the general ring shape.

23. (Currently amended) ~~A mobile telephone~~ An apparatus comprising:

a portable electronic device camera; and

~~a printed wiring board and electrical connector subassembly~~ an apparatus as in claim 19; and, wherein a the portable electronic device camera is coupled to the mobile telephone printed wiring board by the camera electrical connector.

24. (Currently amended) ~~A portable electronic device~~ An apparatus comprising:

Appl. No.: 10/774,821

Reply to Office Action of: 05/29/2008

a device printed wiring board;

an electrical connector connected to the device printed wiring board, wherein the electrical connector has a camera receiving slot; and

a camera coupled to the printed wiring board by the electrical connector, wherein a housing of the camera is located partially inside the camera receiving area to provide a substantially stationery telescoping connection with a partially coplanar height, wherein the housing comprises a plastic material, wherein the camera comprises electrical conductors on a portion of a side of the housing, wherein the electrical conductors directly contact electrical contacts of the electrical connector, and wherein a height of the portion of the side of the housing comprising the electrical conductors extend along a majority of the height of the camera is greater than a height of the electrical connector.

25. (Currently amended) ~~A portable electronic device~~ An apparatus as in claim 24 wherein the electrical connector comprises a housing with a general ring shape and wherein the camera receiving slot is located inside the general ring shape.

26. (Currently amended) ~~A portable electronic device~~ An apparatus as in claim 24 wherein the electrical connector comprises electrical spring contacts extending into a lateral side of the camera receiving slot.

27. (Currently amended) ~~A portable electronic device~~ An apparatus as in claim 26 wherein the electrical spring

Appl. No.: 10/774,821

Reply to Office Action of: 05/29/2008

contacts extend into the camera receiving slot from two opposite lateral sides.

28. (Currently amended) ~~A portable electronic device~~ An apparatus as in claim 24 wherein the electrical conductors are disposed on at least one lateral side of the housing of the camera which are located inside the camera receiving slot.

29. (Currently amended) ~~A portable electronic device~~ An apparatus as in claim 28 wherein the electrical conductors comprises metallized conductors formed on exterior sides of the housing of the camera.

30. (Currently amended) ~~A portable electronic device~~ An apparatus as in claim 24 wherein the ~~portable electronic device~~ apparatus comprises means for locating the camera at a plurality of different heights relative to the device printed wiring board.

31. (Currently amended) ~~A portable electronic device~~ An apparatus as in claim 30 wherein the means for locating the camera comprises the camera extending through a slot in the device printed wiring board.

32. (Currently amended) ~~A portable electronic device~~ An apparatus as in claim 24 wherein the portable electronic device comprises a mobile telephone with a transceiver connected to the device printed wiring board.

33. (Currently amended) A method ~~of assembling a portable electronic device~~ comprising:

Appl. No.: 10/774,821

Reply to Office Action of: 05/29/2008

providing an electrical connector on a printed wiring board;

inserting a camera into a slot through the electrical connector; and

making electrical connection between the electrical connector and electrical conductors extending along a majority of a height of a first lateral side of the camera inside the slot of the electrical connector, wherein a height of the electrical conductors extending along the majority of the height of the first lateral side of the camera is greater than a height of the electrical connector.

34. (Original) A method as in claim 33 wherein the step of inserting the camera through the slot of the electrical connector also comprises inserting the camera through a slot of the printed wiring board.

35. (Previously presented) A method as in claim 33 wherein the step of making electrical connection between the electrical connector and the camera comprises the electrical conductors on the first lateral side of the camera contacting spring contacts of the electrical connector inside the slot of the electrical connector.

36. (Previously presented) A method as in claim 33 wherein the step of making electrical connection between the electrical connector and the camera comprises sliding the electrical conductors of the camera along electrical contacts of the electrical connector along an insertion path of the camera into the slot of the electrical connector.

Appl. No.: 10/774,821

Reply to Office Action of: 05/29/2008

37. (Currently amended) An ~~electronic device~~ apparatus comprising:

a device printed wiring board having a slot therethrough;
and

a camera extending through the slot in the device printed wiring board and coupled to the device printed wiring board by a stepless movement variable height connection,

wherein the stepless movable height connection comprises a first portion connected to the device printed wiring board and a second portion connected to the camera, wherein a height of the second portion extends beyond a height of the first portion, wherein the stepless movement variable height connection allows the camera to slide relative to the device printed wiring board along a first axis to allow positioning of the camera relative to the device printed wiring board at one of a plurality of different heights along the first axis, wherein the plurality of different heights extends along a majority of a height of the camera, and wherein the majority of the height of the camera is greater than a height of the first portion.

38. (Currently amended) An ~~electronic device~~ apparatus as in claim 37 wherein the device printed wiring board comprises contact pads at the slot and the camera comprises spring contacts in the slot and slidable along the contact pads.